



## SPECIFICATION

**NAME :** Down Burn Type Hot water Boiler - Diesel

**FUEL :** Diesel

**MODEL :** KW-60



Type		KW-60	
Heat output		Kcal/h	60000
Water flow rate(50°Cvertical lift)		ℓ/h	1200
Boiler body	Type	--	Vertical chimney
	Water content	ℓ	184
	Heat surface area	m <sup>2</sup>	2.5
	Turbulent plate	--	SUS304 Vross type
	Max working pressure	kg/cm <sup>2</sup>	5
	Proformance	kg/cm <sup>2</sup>	92%
Burner	Combustion method	--	Automatic burner (force draft fan)
	Type	--	Z1
	Fuel consumption	Nm <sup>3</sup> /h	7.8
	Power source	--	1ψ220V
	Ignition system	--	High electric spark
	Motor output	KW	0.2
Control	Combustion control	--	Automatic control
	Temperature control	--	Water temperature control
	Safety devices	--	Flame detection, temperature controler, pressure switch and safety combustion protection
Connection	Feed water pipe	mm	40
	Feedback water pipe	mm	40
	Cold water pipe	mm	40
	Blowdown pipe	mm	40
	Fuel pipe	mm	15
Chimney diameter (outside)		mm	150
Net weight		Kg	306
Running weight		Kg	490

### NOTES :

1. Fuel consumption is calculated at low heat level : Diesel 8400 Kcal/l.
2. Products may be changed for improvement without notice.